



TYRE APPLICATION GUIDE

READ CAREFULLY BEFORE INSTALLATION

LiquiTube™ must be allowed to thoroughly coat the inside of the tyre and rim before complete tyre protection is received. It is important to either drive the vehicle or rotate the tyre slowly several times after installation. Works with most low tyre pressure indicator sensors. Not recommended for use with low tyre pressure equaliser systems.

Note: Do not install in tyres containing water, anti-freeze, calcium chloride or any other liquid ballast or other sealants, as LiquiTube™ is water soluble and may become ineffective.

www.proquip.com.au

- If needed, all high speed road tyres should be balanced before applying LiquiTube™.
- To re-balance tyre: Remove wheel weights. Mount tyre on spin balancer. Hand spin several times to insure LiquiTube™ is evenly distributed throughout the inside of the tyre. Start spin balancer. Take first readings, apply wheel weights, and remount on vehicle. **DO NOT START AND STOP SPIN BALANCER!**
- Some high speed tyres may experience a slight vibration at extreme highway speeds.
- **CAUTION:** DO NOT OVER APPLY LiquiTube™ TO HIGH SPEED TYRES. (Tyres travelling at speeds above 65kph.)

WARNING

- SAME SIZE TYRES MAY BE FOUND IN DIFFERENT SECTIONS
- BE SURE TO CHOOSE THE SECTION WITH THE PROPER HEADING: ROAD TYRES or OFF ROAD TYRES

ROAD TYRES

Cars, Light Trucks, 4WDs

Formula for tyre sizes not found is the tyre height multiplied by the full tyre width, cm x cm x 0.17 will give millilitres.

Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.
12 in. Rims		155-80-13	150	215-65-14	240	325-50-15	420	195-70-15	210	255-50-16	300	17 in. Rims	
165-70-12	150	165-80-13	150	175-70-14	180	195-55-15	210	205-70-15	240	265-50-16	330	285-35-17	300
175-70-12	150	175-80-13	180	185-70-14	180	205-55-15	210	215-70-15	240	275-50-16	330	315-35-17	390
145-80-12	150	185-80-13	180	195-70-14	210	225-55-15	240	225-70-15	270	295-50-16	360	335-35-17	390
155-80-12	150			205-70-14	240	255-55-15	300	235-70-15	300	205-55-16	240	245-40-17	270
		14 in. Rims		215-70-14	240	185-60-15	180	245-70-15	300	215-55-16	240	275-40-17	300
		225-50-14	240	225-70-14	270	195-60-15	210	255-70-15	330	225-55-16	270	285-40-17	330
		245-50-14	270	235-70-14	270	205-60-15	210	265-70-15	360	235-55-16	270	225-45-17	240
		265-50-14	300	245-70-14	300	215-60-15	240	275-70-15	360	205-60-16	240	235-45-17	270
		255-55-14	300	175-75-14	180	225-60-15	240	195-75-15	210	215-60-16	240	245-45-17	270
		175-60-14	150	185-75-14	210	235-60-15	270	205-75-15	240	225-60-16	270	255-45-17	300
		185-60-14	180	195-75-14	210	245-60-15	270	215-75-15	270	235-60-16	270	305-45-17	360
		195-60-14	180	205-75-14	240			225-75-15	270	215-65-16	270	315-45-17	390
		205-60-14	210	215-75-14	240	15 in. Rims		235-75-15	300	275-65-16	360	215-50-17	240
		215-60-14	240	225-75-14	270	255-50-15	300	265-75-15	360	225-70-16	300	245-50-17	300
		225-60-14	240			265-60-15	330			235-70-16	300	255-50-17	300
		235-60-14	270	15 in. Rims		275-60-15	330	16 in. Rims		245-70-16	330	225-55-17	270
		245-60-14	270	195-50-15	180	295-60-15	390	205-40-16	210	255-70-16	330	235-55-17	300
		255-60-14	300	205-50-15	210	185-65-15	180	245-45-16	270	265-70-16	360	255-55-17	330
		265-60-14	300	225-50-15	240	195-65-15	210	265-45-16	300	275-70-16	390	255-60-17	330
		275-60-14	330	245-50-15	270	205-65-15	240	195-50-16	210	225-75-16	270	275-60-17	360
		165-65-13	150	165-65-14	150	215-65-15	240	205-50-16	210	245-75-16	330	235-65-17	300
		195-65-13	180	175-65-14	180	275-50-15	330	225-50-16	240	265-75-16	360	275-65-17	390
		155-70-13	150	185-65-14	180	295-50-15	360	235-50-16	270	155-80-16	180	265-70-17	390
		165-70-13	150	195-65-14	180	305-50-15	360	185-70-15	210				
		175-70-13	180										
		185-70-13	180										
		195-70-13	210										
		205-70-13	210										
		145-80-13	120										

Heavy Duty Trucks

Formula for tyre sizes not found is the tyre height multiplied by the full tyre width, cm x cm x 0.46 will give millilitres.

Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.
14 in. Rims		8.25-16	900	7.50-17.5	900	305-70-19.5	1290	10.00-20	1320	425-65-22.5	2100	12.5-22.5	1650
MH 7.00-14.5	570	9.00-16	960	8.00-17.5	900	445-70-19.5	2190	11.00-20	1440	445-65-22.5	2340	12.75-22.5	1500
MH 8.00-14.5	660	10.00-16	1170	9.00-17.5	960	8.00-19.5	840	11.50-20	1470	255-70-22.5	1140	13.00-22.5	1650
MH 9.00-14.5	780			10.00-17.5	900	15.00-19.5	1800	12.00-20	1620	275-70-22.5	1320	15.00-22.5	1920
		16.5 in. Rims		11.00-17.5	1200	16.5-19.5	2040	13.00-20	1800	245-75-22.5	1050	16.00-22.5	2100
		8.00-16.5	900	14.00-17.5	1440	18.00-19.5	2100	14.00-20	2100	265-75-22.5	1140	16.5-22.5	2100
		8.75-16.5	960			19.5-19.5	2550	16.00-20	2550	295-75-22.5	1380	18.00-22.5	2400
		9.50-16.5	960	18 in. Rims		ML 15-19.5	1800			305-75-22.5	1380		
		10.00-16.5	1170	7.00-18	900	ML 18-19.5	2250	22 in. Rims		275-80-22.5	1380	24 in. Rims	
		12.00-16.5	1320	8.25-18	1200			10.00-22	1410	305-85-22.5	1500	10.00-24	1800
				10.00-18	1200	20 in. Rims		11.00-22	1500	8.00-22.5	870	11.00-24	1590
		17 in. Rims				395-85-20	2100	12.00-22	1650	9.00-22.5	1050	12.00-24	1800
		7.00-17	900	19.5 in. Rims	ml	7.50-20	900			10.00-22.5	1200	13.00-24	1950
				225-70-19.5	840	8.00-20	1050	22.5 in. Rims		11.00-22.5	1350	14.00-24	2100
		17.5 in. Rims		245-70-19.5	960	8.25-20	1050	445-50-22.5	2100	11.50-22.5	1350	ML 14.00-24	2400
		7.00-17.5	900	265-70-19.5	1020	9.00-20	1140	385-65-22.5	1920	12.00-22.5	1470		

Trailer Tyres & Powered Equipment

Formula for tyre sizes not found is the tyre height multiplied by the full tyre width, cm x cm x 0.46 will give millilitres.

Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.
8 in. Rims		10 in. Rims		13 in. Rims		7.9 - 14	480	15 in. Rims		8.25-15	600	6.50-16	600
4.8-8	300	6.50-10	480	6.00-13	450	8.25 - 14	600	C78-15	600	8.55-15	600	7.00 - 16	600
5.70-8	300	7.00-10	480	6.50-13	450	8.55 - 14	600	G78-15	600	8.85-15	600	7.50 - 16	600
16.6-6.5-8	300	7.50-10	480	7.00-13	450	11-14	600	H78-15	600	9.00-15	600	8.00 - 16	600
18.5-8.5-8	480	20.5-8.0-10	480					L78-15	600	10.00-15	600	8.25 - 16	750
18.5-9.5-8	480	20.5-50-10	420	14 in. Rims		14.5 in. Rims		6.70-15	690	11.00-15	600	9.00 - 16	750
				E78 - 14	480	7.00 - 14.5	600	6.85-15	600	12.00-15	600	10.00 - 16	750
		12 in. Rims		G78 - 14	480	8.00 - 14.5	600	7.00-15	600			11.00 - 16	750
		4.80-12	300	6.45 - 14	450	9.00 - 14.5	600	7.10-15	600	16 in. Rims			
		5.30-12	360	7.00 - 14	540			7.35-15	600	F78-16	600	16.5 in. Rims	
		6.90-12	450	7.35 - 14	450			7.50-15	600	H78-16	600	8.00 - 16.5	750
		23.5-8.5-12	600	7.75 - 14	450			7.75-15	600	6.00-16	600	8.75 - 16.5	750

OFF ROAD TYRES

Formula for tyre sizes not found is the tyre height multiplied by the full tyre width, cm x cm x 0.92 will give millilitres.

Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.	Tyre Size	ml.				
4 in. Rims		22.00-7-9	840	14 in. Rims		9.50-16	2100	10.00-20	2700	24.5 in Rims		18.40-30	7500	42 in. Rims		9.50-42	4980
2.50-4	180	22.00-10-9	1200	4.00-14	750	10.00-16	2340	10.30-20	2700	11.00-24.5	3900	21.00-30	8100	9.50-42	4980	12.40-42	5220
2.80-4	240	22.00-11-9	1260	6.00-14	1080	11.00-16	2700	10.50-20	3000	12.00-24.5	3900	23.10-30	10380	12.40-42	5220	18.40-42	9000
4.10-4	240	22.00-12-9	1320	7.00-14	1200	11.1-16	2700	11.00-20	2700	13.50-24.5	4320	67-34-30	15980	18.40-42	9000	18.90-42	9300
9-3.50-4	240	24.00-13-9	1380	7.50-14	1350	11.20-16	2700	11.20-20	3000			540-65-30	8220	18.90-42	9300	20.80-42	9900
11-4.00-4	360	25.00-11-9	1440	8.00-14	1350	11.50-16	2880	11.50-20	3000	25 in. Rims		480-70-30	7200	20.80-42	9900	900-50-42	17700
		25.00-12-9	2000	8.50-14	1800	12.40-16	3060	12.00-20	3300	7.5-25	2700	380-85-30	5700	900-50-42	17700	650-65-42	12600
5 in. Rims		25.00-13-9	1500	9.00-14	1650	12.50-16	2940	12.50-20	3300	11.00-25	3900	420-90-30	6600	650-65-42	12600	580-70-42	11040
3.40-5	240			9.50-14	1800	12.5L-16	2940	13.00-20	3300	12.00-25	3900			620-70-42	12360	710-70-42	15000
4.10-5	360	10 in. Rims		9.5L-14	1800	13.60-16	3060	14.00-20	3900	13.00-25	4380	32 in. Rims		710-70-42	15000	480-80-42	9000
4.10-3.50-5	300	3.00-10	540	11.00-14	1950	18.4-16	5400	16.00-20	4500	14.00-25	4500	8.30-32	2940	520-85-42	10320	30.50-32	14400
10-4.5-5	300	3.50-10	540	11 L-14	2100	33-9.50-16	2400	18.00-20	5100	15.50-25	4800	9.50-32	3120			30.5L-32	14400
10.50-5-5	300	4.50-10	600	13.00-14	2400	225-75-16	900	24.00-20	6300	16.00-25	5100	12.40-32	4440			30.50-32	14400
11-3.50-5	300	6.50-10	1050	23-8.50-14	1380	245-75-16	900	38-14.00-20	3780	17.50-25	5640	16.90-32	7200			35.0-32	14400
11-4.00-5	300	7.00-10	1050	25-3.50-14	1500	265-75-16	900	38-18.00-20	4860	18.00-25	7800	24.50-32	11400	43 in. Rims		30.50-32	14100
11-4.50-5	300	7.50-10	1140	70-14	1080	225-75-16	900	41-14.00-20	3540	20.50-25	7800	30.00-32	14100	24.00-43	15000	30.5L-32	14400
11-6.00-5	480	9.00-10	1320	78-14	1080	215-85-16	900	42-25.00-20	6300	21.00-25	7920	30.5L-32	14400			30.50-32	14400
11-7.00-5	600	15.00-10	1440			225-85-16	900	44-18.00*-20	4800	22.00-25	8280	30.50-32	14400	45 in. Rims		35.0-32	14400
11-7.50-5	600	18-9.50-10	1080	15 in. Rims		235-85-16	900	44-41.00-20	12000	23.50-25	9360	35.0-32	14400	65-45-45	30000	35.0-32	14400
13-5.00-5	600	18-9.80-10	1080	4.00-15	780	255-85-16	900	47-25.00-20	8100	24.00-25	11100	35.0-32	16500	45-65-45	25800	35.0-32	14400
		18-10-10	1080	5.00-15	900			48-25.00-20	8580	26.50-25	11400	73-44.00-32	16800			35.0-32	14400
6 in. Rims		18-10.50-10	1080	5.50-15	960	16.1 in. Rims		48-26.50-20	9000	29.50-25	12000	68-50-32	24000	46 in. Rims		35.0-32	14400
4.00-6	480	18-11-10	1140	5.70-15	1020	13.50-16.1	3840	48-31.00-20	9300	33.25-25	12600	73-50-32	25800	13.60-46	6300	35.0-32	14400
4.10-6	480	20-7.50-10	780	5.90-15	1080	14-16.1	3900	50-20.00-20	5880	61.00-18-25	13200	14.90-46	7080	14.90-46	7080	30.00-32	14100
4.10-3.50-6	480	20-8-10	840	6.00-15	1140	14.5-75-16.1	3690			67.00-34-25	15000	18.40-46	9360	18.40-46	9360	30.5L-32	14400
5.30-6	600	20-10-10	960	6.40-15	1200	16.5-16.1	4800	21 in. Rims		660-34-25	15000	620-70-46	12900	620-70-46	12900	30.5L-32	14400
6.90-6.00-6	660	20-11-10	960	6.70-15	1260	18.4-16.1	5580	27.25-21	8400	670-34-25	15000	420-80-46	7980	420-80-46	7980	30.5L-32	14400
8.00-6	660	20-12-10	1020	7.00L-15	1560	19L-16.1	5580			54.00-37-25	12900	480-80-46	9600	480-80-46	9600	30.5L-32	14400
12.00-6.00-6	660	20-14-10	1050	7.50-15	1560	21.5-16.1	6600	22 in. Rims		66.00-43-25	13800	340-85-46	6120	340-85-46	6120	30.5L-32	14400
12.00-8.00-6	660	20.5-10	1050	7.5L-15	1560	35-19-16.1	3750	7.50-22	2100	66.00-44-25	14400	520-85-46	11100	520-85-46	11100	30.5L-32	14400
12.00-11.00-6	780	20.5-7-10	1080	7.60-15	1620	38-20-16.1	5220	8.50-22	2400	25.00-55-25	9600	320-90-46	5700	320-90-46	5700	30.5L-32	14400
13-5.00-6	390	20.5-8-10	1080	8.15-15	1680	42-16.53-16.1	4500	10.00-22	2820	22.00-65-25	10500	380-90-46	7200	380-90-46	7200	30.5L-32	14400
13-6.00-6	450	21-7-10	840	8.25-15	1740	45-18.42-16.1	5100	11.00-22	2820	25.00-65-25	9000	230-95-46	3900	230-95-46	3900	30.5L-32	14400
13-6.50-6	600	21-8-10	900	8.5-90-15	1620	45-21.5L-16.1	6000	12.00-22	3000	30.00-65-25	11640					30.5L-32	14400
14-4.50-6	420	21-9-10	960	9.00-15	1800					555-65-25	7020					30.5L-32	14400
14-6.00-6	600	21-12.5-10	1020	9.50-15	1860	16.5 in. Rims		22.5 in. Rims		23.00-80-25	10500	34 in. Rims		23.00-80-25	10500	34.00-32	14400
14-8.00-6	780	22-7-10	1050	9.5L-15	1920	10-16.5	2340	8.00-22.5	2280	4.45-80-25	6600	11.20-34	4500	4.45-80-25	6600	34.00-32	14400
15-6.00-6	660	22-8-10	1050	9.70-15	1980	12-16.5	2580	9.00-22.5	2340	5.25-80-25	7260	12.40-34	5100	5.25-80-25	7260	34.00-32	14400
16.00-4.50-6	480	22-9-10	1080	10.00-15	2100	30.5-12.5-16.5	2580	10.00-22.5	2820	6.05-80-25	9150	14.90-34	5700	6.05-80-25	9150	34.00-32	14400
145-70-6	450	22-10-10	1080	11.00-15	2160	31-11.5-16.5	2700	11.00-22.5	2880	23.00-90-25	10500	16.90-34	6900	23.00-90-25	10500	34.00-32	14400
		22-11-10	1110	11L-15	2160	33-12.5-16.5	2880	11.50-22.5	2940	385-95-25	4860	18.40-34	7500	385-95-25	4860	34.00-32	14400
7 in. Rims		23-7-10	1110	12.2L-15	2400	33-14.5-16.5	2940	12.00-22.5	3000	445-95-25	7200	18.50-34	7800	445-95-25	7200	34.00-32	14400
4.50-7	480	23-8-10	1140	12.50-15	2400	35-14.5-16.5	2940	12.50-22.5	3060			20.80-34	9480			34.00-32	14400
4.80-7	480	23-9-10	1140	13.50-15	2700	36.5-12.5-16.5	2820	13.00-22.5	3120	26 in. Rims		23.10-34	11040	50 in. Rims		23.10-34	11040
		23-10-10	1200	14.50L-15	3000			15.00-22.5	3180	12.40-26	4500	600-65-34	7200	480-80-50	9960	600-65-34	7200
8 in. Rims		24-11-10	1280	18.25-15	3600	16.7 in. Rims		15.50-22.5	3180	13.60-26	4800	480-70-34	7500	320-90-50	6000	480-70-34	7500
ALL GOLF CARS	600	25-8-10	1200	25-7.50-15	1320	14L-16.7	3300	16.00-22.5	3300	14.90-26	5160	520-70-34	8400			520-70-34	8400
4.00-8	480	25-11-10	1320	25-9-15	1380			16.50-22.5	3360	16.90-26	6180	650-75-34	12150	51 in. Rims		650-75-34	12150
4.30-8	480	25-12-10	1440	25-10.5-15	1500	17 in. Rims		18.00-22.5	3780	18.00-26	7020	710-75-34	14160	24.00-51	19200	710-75-34	14160
4.80-8	480	27-9-10	1620	25-12.5-15	1800	7.00-17	1260	385-85-22.5	3000	18.40-26	7020	320-85-34	4680	27.00-51	19500	320-85-34	4680
5.00-8	660	27-15-10	2040	27-7.50-15	1440	7.50-17	1440	425-65-22.5	3300	23.10-26	9840	380-85-34	5700	30.00-51	22380	380-85-34	5700
5.70-8	660			27-8.50-15	1560	8.25-17	1440	445-65-22.5	3300	24.00-26	9840	250-95-34	3480	33.00-51	25200	250-95-34	3480
6.00-8	660	101/2 in. Rims		27-9.50-15	1680			255-70-22.5	2520	28.00-26	10500	36.00-51	27000	36.00-51	27000	28.00-26	10500
11-4.00-8	480	23-10.5	1380	27-10.50-15	1290	17.5 in. Rims		275-70-22.5	2520	28L-26	10800	37.00-51	27900	37.00-51	27900	28L-26	10800
16-5.00-8	600			28-9-15	1740	7.00-17.5	1260	365-70-22.5	3000	54-31.00-26	11700	37.00-51	28200	37.00-51	28200	54-31.00-26	11700
16-5.50-8	660	11 in. Rims		28-12-15	2040	8.00-17.5											